

- VLF
- DC
- Jacket/Sheath
- Sheath Fault Location mode³
- Fault conditioning
- DDD®
Dual Discharge Device (internal)
- USB Data Transfer

b2 High-Voltage
is a business division of
b2 electronic GmbH

Riedstraße 1
6833 Klaus
AUSTRIA

Tel. +43 (0)5523 57373
Fax + 43 (0)5523 57373-5

www.b2hv.at
info@b2hv.at



DHV1235 Rev02
ENGLISH

Subject to alternations-
errors excepted

HVA94

Compact and universal VLF High Voltage Test Set

Large output load capability up to 10 μF ¹

The high power HVA94 Test System is capable of testing cables up to 3,300 m

- 1 μF at 0.1 Hz and 61 kV rms
- 0.85 μF at 0.1 Hz and 66 kV rms.

The variable output frequency allows the testing of even much longer cables.



Type	HVA94	
Article number	SH0211	
Input Voltage	210 – 240 V 50/60 Hz (3.0 kVA)	
Output Voltage	Sinusoidal	0 – 94 kV peak, 66 kV rms
	DC	± 0 – 90 kV
	Squarewave	90 kV
	Vacuum Bottle	90 kV
	Accuracy	± 1 %
	Resolution	0.1 kV
Output Current	0 – 65 mA (Resolution 1 μA) Accuracy: ± 1 %	
Resistance Range	0.1 M Ω ...5 G Ω	
Sheath Test	U _{max}	10 kV
	Duration	1 min – 15 min
	Trip Current	0.1 mA – 5.0 mA
Sheath Fault Location ³	Un _{max}	10 kV
	Duration	1 min – 60 min
	Pulse/Period	1:3 / 4 s, 1:5 / 4 s, 1:5 / 6 s, 1:9 / 6 s
Output Frequency	0.01 ... 0.1 Hz in steps of 0.01 Hz (default 0.1 Hz) – auto frequency selection	
Output Load	0.85 μF @ 0.1 Hz @ 66 kV rms (Approx 3,400 m of cable) ² 1.0 μF @ 0.1 Hz @ 61 kV rms (Approx 4,000 m of cable) ² 8,5 μF @ 0.01 Hz @ 66 kV rms (Approx 34,000 m of cable) ² 10 μF maximum Capacitance ¹	
Output Modes	AC (VLF) Symmetrical and load independent across full range, DC (plus or negative polarity), Burn-/ Fault Condition or Fault Trip Mode, Jacket / Sheath Testing	
Safety	50 Hz 12 kV Feedback Protection / Discharge unit	
Memory	50 Test Records Stored	
Metering	Voltage an Current (True rms and / or peak), Capacitance, Resistance, Time, Flashover Voltage	
Duty	Continuous! No thermal limitation for operating time.	
HV Cable	7.5 m with Alligator clamps on end (other options available on request)	
Software	„HVA Control Center“	
Computer interfaces	RS232	•
	USB	•
Environmental conditions	Storage: -25°C to + 70°C, Operating: -5°C to + 45°C	
Dimensions L x W x H	650 x 445 x 610 mm (Excl. Carry Handle), also as 19" version available	
Weight	128 kg	
Upgrades (Optional)	Tan Delta TD90-MC, Partial Discharge System PD90-2 / PDTD90-2	

¹ At lower frequency and voltage

² Based on a typical cable: 250 pF/m

³ In combination with locator set (not in scope of supply)